

Canon**XF705**

ROZLIŠENÍ	VZORKOVÁNÍ BAREV	BITOVÁ HLOUBKA	SNÍMKOVÁ FREKVENCE	KODEK	Mb/s
3840 × 2160	YCC 4:2:2	10 bitů	59,94P, 29,97P, 23,98P, 50,00P, 25,00P	H.265/HEVC	160 Mb/s / 110 Mb/s
1920 × 1080	YCC 4:2:2	10 bitů	59,94P, 29,97P, 23,98P, 50,00P, 25,00P	H.265/HEVC	60 Mb/s / 45 Mb/s
			59,94i, 50,00i		60 Mb/s / 45 Mb/s
			120P, 100P		180 Mb/s
3840 × 2160	YCC 4:2:0	8 bitů	29,97p, 23,98p, 25,00p	H.264/XF-AVC	160 Mb/s
1920 × 1080	YCC 4:2:0	8 bitů	59,94P, 29,97P, 23,98P, 50,00P, 25,00P	H.264/XF-AVC	45 Mb/s
			59,94i, 50,00i	H.264/XF-AVC	35 Mb/s
			120P, 100P	H.264/XF-AVC	45 Mb/s
1280 × 720	YCC 4:2:0	8 bitů	59,94P	H.264/XF-AVC	180 Mb/s
1280 × 720	YCC 4:2:0	8 bitů	59,94P	H.264/XF-AVC	8 Mb/s
1920 × 1080	YCC 4:2:0	8 bitů	59,94P, 29,97P, 23,98P, 50,00P, 25,00P	H.264/MP4	35 Mb/s / 8 Mb/s